Panel Discussion

Can Cross-Layer Techniques Enhance the Performance of Tactical Military Networks

Andrea Goldsmith Stanford University

> NATO Cross-layer Workshop Naval Research Labs June 2, 2004

| maintaining the data needed, and c including suggestions for reducing | lection of information is estimated to completing and reviewing the collect this burden, to Washington Headquuld be aware that notwithstanding and DMB control number. | ion of information. Send comments arters Services, Directorate for Info | regarding this burden estimate rmation Operations and Reports | or any other aspect of the 1215 Jefferson Davis | is collection of information, Highway, Suite 1204, Arlington | |
|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|---------------------------------------------------------------|-------------------------------------------------|-----------------------------------------------------------------|--|
| 1. REPORT DATE 01 DEC 2007 | | | 3. DATES COVERED | | | |
| 4. TITLE AND SUBTITLE Panel Discussion - Can Cross-Layer Techniques Enhance the Performance of Tactical Military Networks? | | | | 5a. CONTRACT NUMBER | | |
| | | | | 5b. GRANT NUMBER | | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | | |
| 6. AUTHOR(S) | | | | 5d. PROJECT NUMBER | | |
| | | | | 5e. TASK NUMBER | | |
| | | | | 5f. WORK UNIT NUMBER | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Stanford University | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER | | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | | |
| | | | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited. | | | | | | |
| 13. SUPPLEMENTARY NOTES | | | | | | |
| 14. ABSTRACT | | | | | | |
| 15. SUBJECT TERMS | | | | | | |
| 16. SECURITY CLASSIFIC | 17. LIMITATION OF | 18. NUMBER | 19a. NAME OF | | | |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | - ABSTRACT UU | OF PAGES 8 | RESPONSIBLE PERSON | |

Report Documentation Page

Form Approved OMB No. 0704-0188

Crosslayer Design: A New Paradigm

- Hardware
- Link
- Access
- Network
- Application

Delay Constraints
Rate Requirements
Energy Constraints
Complexity Constraints
Robustness

Optimize and adapt across design layers
Provide robustness to uncertainty
Use scheduling to reserve resources

Special Considerations of a Military Environment

- Unique considerations for military systems
 - Low performance radios (10s of Kbps in some cases)
 - Heterogeneous equipment with different capabilities
 - Hostile environment (jammers, node destruction)
 - Applications with very different requirements and priorities.
 - Widely varying communication conditions and network topologies
 - Legacy systems
- Can cross layering addresses these considerations
 - Adaptation and diversity can provide robustness to jamming and node destruction and compromise
 - Cross layering supports different requirements and priorities across all layers of the network protocol stack.
 - Cross layering can adjust higher layer protocols to the capabilities of underlying equipment.
 - Cross layering adapts to and provides robustness against variations in the communication capabilities and network topology.
 - Not clear how legacy systems can exploit cross-layer protocols.
 - Some systems must do crosslayering with constraints on some layers.


Impact of energy considerations on cross-layering

- Each node can only send a <u>finite</u> number of bits.
 - Bit allocation must be optimized across all protocol layers
 - Must use energy per bit as performance metric (not power=E/T)
- Short-range networks must consider transmit, circuit, and processing energy.
 - Circuit and processing energy can dominate energy consumption
 - Sophisticated communication and signal processing techniques not necessarily energy-efficient (e.g. high level modulation, coding, etc.)
 - Circuit energy minimized by minimizing bit duration, transmit energy minimized by maximizing bit duration
 - Leads to optimal bit durations and energy vs. delay tradeoffs
 - Sleep modes save energy but complicate many aspects of networking (synchronization, routing, access, sensing functionality, etc.)
- Changes everything about the network design:
 - Delay vs. throughput vs. node/network lifetime tradeoffs.
 - Brings "hardware layer" into the protocol stack


To Cross-Layer or Not

- Layering is not evil
 - Reduces complexity and provides design abstractions
 - Has worked well in the Internet, and is not going away
- Cross-layer design is not about eliminating layers, but about designing across them
 - Gains possible for both wireless and wired networks
 - Some types of networks and applications will benefit more than others
 - Need to determine where significant crosslayer gains are possible
 - Want to avoid negative interations between layers
- Need to address key questions in crosslayering
 - What is the right framework for crosslayer design
 - What information to exchange across layers, and how to use it
 - How to balance adaptivity, diversity, and scheduling
 - What are the key crosslayer synergies: how many layers to involve
 - How to avoid unexpected interactions across layers
 - How to manage cross-layer complexity
 - How to deal with legacy systems and protocols

Ad-Hoc vs. Sensor Networks



- Peer-to-peer with no backbone infrastructure.
- Nodes often mobile
- Nodes generate independent information
- Can require high data rates
- Typically support multiple applications
- Peak or average power constraints



- Data flows to a centralized location
- Nodes often stationary
- Node information correlated in time/space
- Low per-node rates but 10s to 1000s of nodes
- Typically support a single application
- Energy a driving constraint

Cross-Layer Gains: Ad-hoc vs. Sensor Networks

- Both types of networks can benefit from cross-layer design, but probably sensor networks more than ad-hoc networks.
- Stand-alone networks designed for one dedicated purpose have the most to gain from cross-layer design.
- Ad-hoc networks may be more constrained by existing standards and interoperability, which make cross-layer design more difficult.
- Mobility in ad hoc networks make adaptivity and scheduling difficult, and robustness critical.
- A driving energy constraint, typical in sensor networks, makes cross-layer design imperative.
- Performance gains of an order of magnitude or more in both types of networks are possible.

Research Agenda

- Pursue both broad cross-layer design frameworks and tailored cross layer designs for specific applications
 - We don't have sufficient insight to see big picture yet
 - Just starting to ask the right questions, but don't necessarily know how to answer them yet
- Further explore adaptivity, diversity, and scheduling in a cross-layer context
- Networks with energy-constrained nodes.
 - What are appropriate abstractions, especially for H/W
 - What is the right cross-layer framework
 - How does application layer/compression come in
- Collaborative transmission and signal processing for sensor networks.